
Heating, Ventilation and Air Conditioning Applications Combustion Control Products for HVAC







Burner & Efficiency Controls

Flame Safeguard Controls





- BurnerPro[™]
- BurnerLogix®
- Flame-Monitor™
- MicroM

Efficiency Controls



- Nexus[®] NXF4000
- Nexus PPC4000
- Nexus NX6100
- Nexus PPC6000

CM-420 Combustion Monitor

Provides oxygen percentage via 4-20mA or Modbus for PLC, Scada or building management systems. Used in conjunction with the Fireye oxygen probe (NXCESO2).

Flame Scanners

Discrete Flame Scanners



- UV1A (Ultraviolet)
- UV90L (Ultraviolet)
- 45UV5 (Ultraviolet / Self Check)
- 48PT2 (Infrared)

Integrated Flame Scanners



- Phoenix[™] Series 2 (Ultraviolet Extended, Ultraviolet or Infrared)
- InSight[®] II (Ultraviolet, Infrared or Dual Sensor)
- InSight Series 4 (Ultraviolet or Infrared)

FX Servo Motors



The Fireye FX Series servo motors are precision actuators designed to accurately position valves and dampers.

Flame Rods

The Fireye flame rod (69ND1) is made from high temperature resistant metal and can be used to detect gas flames only.

Oxygen Probe



The Fireye oxygen probe (NXCESO2) is designed to provide continuous oxygen concentration readings.



fireye.com

MF-00-2-000F-0-014-B (2022/05) All trademarks and service marks referred herein are property of their respective owners. ©2022 Carrier. All Rights Reserved. A Carrier Company

fireye

CM-420

Join us on in







For more information, please <u>contact</u> your local OEM or Fireye Distributor.