

Nexus® Combustion Efficiency Systems Training & Demo Units



Nexus 4000 & 6000 Series Trainers NX-ATU-4000 / NX-ATU-6000

Training or demo units for Nexus efficiency and parallel positioning controls

The Nexus training and demo units (NX-ATU-4000 or NX-ATU-6000) provide users with the ability to familiarize themselves with the functions and features of the Nexus NXF4000, PPC4000, NX6100 and PPC6000 controller range.

Features

- Indicator lights for sequence of operation
- Digital input switches simulating safety signals
- Auto / manual switches for airflow, POC, and flame signals
- Two analog PV simulator included (4-20mA)
- Includes VFD card and flame amplifier
- 120VAC standard with 220VAC option
- Display: Touchscreen display (NX-ATU-4000), OLED display (NX-ATU-6000)
- Pelican case suitable for either NX-ATU-4000 or NX-ATU-6000 (NX-ATU-HC)
 - Size: 32" W x 22" L x 19" D (812mm W x 558mm L 482mm D)
 - Weight: 70lbs (31kg), including foam-lined shipping box

NX-ATU-4000



Compatible with Nexus NXF4000 efficiency controller and Nexus PPC4000 parallel positioning controller. Complete with touchscreen display.

NX-ATU-6000



Compatible with Nexus NX6100 efficiency controller and Nexus PPC6000 parallel positioning controller. Complete with OLED display

For more information, please [contact](#) your local Fireeye Distributor.

fireeye.com

MF-00-2-0100-0-049-B (2023/03)

All trademarks and service marks referred herein are property of their respective owners.

©2023 Carrier. All Rights Reserved. A Carrier Company

Join us on

