

## TECHNICAL SPECIFICATIONS

<b>Supply Voltage:</b>	120/230 VAC, 50/60Hz
<b>Power Consumption:</b>	Approx. 15VA (with Keypad display attached & no accessories)
<b>Ambient Temperature Range:</b>	32° to 140°F (0° to 60°C)
<b>Typical Loads:</b>	Display: 6 VA O2 Probe: 12 VA FX04: 5 VA FX20: 15 VA FX50: 20 VA
<b>Branch Circuit:</b>	2000 VA
<b>Dimensions:</b>	
<b>Control Unit:</b>	5.0" (127mm) wide x 8.0" (203mm) high x 4.0" (102mm) deep
<b>Weight:</b>	2.25 lbs (1.02kg)

## FEATURES/BENEFITS

Requires flame safeguard system like the Burnerlogix® or Flame Monitor®

- Increased Efficiency
- Reduce fuel consumption
- Reduce emissions & Greenhouse gases
- Reduce downtime & maintenance

## PPC4000 Air/Fuel Ratio Control



### *The Combustion Control Specialists*

3 Manchester Rd. • Derry, NH 03038 • USA  
Tel: 603 - 432 - 4100 • Fax: 603 - 432 - 1570  
[www.fireeye.com](http://www.fireeye.com)

## TECHNICAL SPECIFICATIONS

<b>Supply Voltage:</b>	120/230 VAC, 50/60Hz
<b>Power Consumption:</b>	Approx. 15VA (with display attached & no accessories)
<b>Ambient Temperature Range:</b>	32° to 140°F (0° to 60°C)
<b>Typical Loads:</b>	Display: 6 VA O2 Probe: 12 VA FX04: 5 VA FX20: 15 VA FX50: 20 VA
<b>Branch Circuit:</b>	2000 VA
<b>Dimensions:</b>	5.0" (127mm) wide x 8.0" (203mm) high x 4.0" (102mm) deep
<b>Control Unit:</b>	
<b>Weight:</b>	2.25 lbs (1.02kg)

## FEATURES/BENEFITS

### Integrated Parallel Positioning and Burner Management control

- Increased Efficiency
- Reduce fuel consumption
- Reduce emissions & Greenhouse gases
- Reduce downtime & maintenance

**ELIMINATES EXTERNAL  
FLAME SAFEGUARD**

## NXF4000 Advanced Burner Management System w/ Parallel Positioning & Integrated Flame Safeguard



United Technologies

### The Combustion Control Specialists

3 Manchester Rd. • Derry, NH 03038 • USA  
Tel: 603 - 432 - 4100 • Fax: 603 - 432 - 1570

[www.fireeye.com](http://www.fireeye.com)